Technical Data Sheet

Making Life More Colourful...

Over 60 years of colour matching experience, over 60 years of achieving customer expectations and over 60 years of supplying industry with the colour it needs.

Issue Date: 18/05/2016

Polyether Polyol Matched Shade Pigment Dispersions

WSL

Product Description:

Polyether Polyol-based colour concentrates suitable for use with Rigid / Semi-Rigid Elastomer Systems



FM20877



FMS566219

Available Colours:

We offer various shades from internationally-recognised colour ranges such as RAL & British Standard as well as a bespoke colour-matching service.

Technical Properties: All products are tested in accordance with our ISO9001:2008 Certification			
Properties	Test Method	Test Frequency	Declared Values
Particle Size Evaluation	BS3900: Part C6 (Hegman Gauge)	Every Production Batch	< 15 Microns
Top Shade Evaluation	QCT005 (4% Pigment Addition Level)	Every Production Batch	Same or within commercial tolerance to Master Standard
Tinctorial Strength Evaluation	QCT004 (4% Pigment Addition Level)	Every Production Batch	Same or within commercial tolerance to Master Standard

Application Instruction / Directions for use:

Stir well before use and carry out a colour check on a small scale, prior to using large production quantities. A pigment paste addition rate (by weight) of between 2-5% of polyol component should give sufficient opacity for most applications. Blend thoroughly by hand or low speed mechanical mixer. High speed agitation is best avoided since this may introduce air voids into the final article

Shelf Life / Storage:

Nominal 12 months from date of manufacture as detailed on product labelling. Up to 24 months if stored unopened at an ideal temperature of between 15 & 25°C. Keep out of the reach of children.

Packaging Specifications:

Supplied in HDPE plastic & UN approved metal containers of various sizes. Each container is filled to its specified nett weight with a telerance of +/- 1%.

Pigment Light Fastness & Chemical Resistance:

West & Senior is committed to sourcing & using high quality pigments wherever possible. Our choice of pigments used in the manufacture of matched shades is predominantly Excellent for Light Fastness & Chemical Resistance. Enhanced data is available upon request.

Technical Support:

Through our technical department and laboratories we can offer a comprenensive service to the customer. Technical representatives are available to provide further information.

Health and Safety:

Refer to the West and Senior Material Safety Data Sheet for further information.

West & Senior Limited | Milltown Street | Radcliffe | Manchester | M26 1WE | United Kingdon

Tel: +44 (0) 161 724 7131 | Fax: +44 (0) 161 724 9519 | www.westsenior.co.uk | info@westsenior.co.uk

The information in this Technical Data Sheet (TDS) is believed to be accurate as of the date issued.

West & Senior Limited does not warranty the use or application of the materials it manufactures or supplies.